

CERAMIC WATER PURIFIER CF115W

PERFORMANCE DATA SHEET

Goldstream Sentry Filter (CF115W)			
Operating Pressure Range	Rated Capacity	Operating Temperature Range	Rated Flow
10psi – 125psi	10000L	5°C - 70°C	2.5L/min
KLT Filtration Ltd recommend that the Filter/Purifier is changed at least every six months. The filter should be checked for cleaning every few weeks and cleaned according to the owner's manual.			







BACTERIA

Microbial Contaminant	Influent Challenge	Reduction Requirement (%)	Reduction (%) at 3000L	Reduction (%) at 4500L
<i>Klebsiella terrigena</i>	1.228128x10 ⁶ CFU/L	99.9999	>99.9999	99.9999
<i>Cryptosporidium spp.</i>	1.105220x10 ⁹ oocysts/L	99.9	>99.9	99.9

PARTICLES

99.9% removal of particle reduction class 1, including microplastics.

TESTING INFORMATION

-  Filter is only to be used with cold water.
-  Filter usage must comply with all state and local laws.
-  Testing was performed under standard laboratory conditions, actual performance may vary.
-  Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.
-  See owner's manual for general installation conditions and needs, plus manufacturer's limited warranty.
-  This water filter is not intended to convert waste water or raw sewage into drinking water.

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.

*Envirotek*TM

Independently Tested and Certified
by Envirotek Inc

Coldstream® Filters are independently tested and certified to the following:
NSF/ANSI 42 Aesthetic Effects
See KLT Filtration Ltd lab reports for more detail

GOLD SEAL CERTIFIED